

SPECIFICATION SHEET
JFW MODEL 75FP-XXX-3G
FIXED ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-3000 MHz
Impedance	75 Ohms nominal
Attenuation Values	3 thru 30 dB in any 1 dB increment
VSWR	1.15:1 maximum DC-1 GHz 1.35:1 maximum 1-3 GHz
Attenuation Accuracy	3 thru 20 dB: ± 0.3 dB DC-1300 MHz ± 0.5 dB 1300-3000 MHz 21 thru 30 dB: ± 0.6 dB DC-1300 MHz ± 1.0 dB 1300-3000 MHz
RF Input Power	0.5 Watts average @ +25°C
Peak Power	100 Watts
RF Connector	N or F
Operating Temperature Range	-55°C to +125°C
Physical Size	See outline drawing 092-2189 (N) See outline drawing 092-2757 (F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
300	09/07/1994	A		4658	08/11/2004	D	CLV 08/12/2004
305	09/12/1994	B		17625	08/28/2009	E	SMR 08/28/2009
4521	03/12/2004	C	CLV 03/12/2004	22341	01/10/2013	F	CLK 01/10/2013