



ZONE		REV	DESCRIPTION	DATE	APPROVED

**SPECIFICATIONS**

Frequency Range: 1.12-1.70 GHz  
 Waveguide Size: WR650 (Input)  
 Flange Types: Per Order (-1,-2,-S)  
 VSWR: 1.15:1 Max.  
 Average Power: 8000 Watts

**F = FLANGE TYPES**

- 1 = CPRG
- 2 = CPRF
- S = SPECIAL

**ORDERING INFORMATION**

EXAMPLE PART NUMBER: WL-1-F  
 VERY HIGH POWER SERIES  
 FREQUENCY BAND  
 FLANGE TYPE

Aluminum 6061 High Temp. Black Paint	<b>MCLI</b> <small>UNLESS OTHERWISE SPECIFIED:</small> DIMENSIONS IN INCHES OR FRACTIONS OF INCHES FINISHES: 1. RA DECIMALS: 0.01 0.005 ANGLES: 1/2	QUANTITY: 1 ORDER NO.:	DATE: N/A PRICE: N/A DO NOT SCALE THE DRAWING
		ORDER NO.: PART NO.:	QUANTITY: 1 ORDER NO.:
Pdmoon Luthmahan T. Nguyen	DATE: 05-04-2011 DATE: 05-04-2011	ORDER NO.: PART NO.:	QUANTITY: 1 ORDER NO.:
TERMINATION, WR650 8000 Watts WL-1-F		ORDER NO.: PART NO.:	QUANTITY: 1 ORDER NO.:
0D2L5		ORDER NO.: PART NO.:	QUANTITY: 1 ORDER NO.:
85658		ORDER NO.: PART NO.:	QUANTITY: 1 ORDER NO.: