



Model: AE-H000-40C

Description:.....	Current Controlled PIN Attenuator
Operating Frequency:.....	2.25 – 6.75 GHz
Phase-Invariant Frequency Region ($\lt; \pm 10 \text{ Deg}$):.....	3.05 – 5.0 GHz
Insertion Loss (0dB Attn. Ref.):.....	2.0 dB Max
Attenuation Range:.....	0 – 40 dB Nominal Min
Attenuation Flatness:.....	1.0 dB Peak-Peak up to 10 dB
.....	1.2 dB Peak-Peak up to 20 dB
.....	1.5 dB Peak-Peak up to 30 dB
.....	1.9 dB Peak-Peak up to 40 dB
Control Function:.....	0 – 10 mA Forward Current (approx.)
VSWR (all settings):.....	1.5:1 Max
Settling Time ("±1dB of Target Setting"):.....	500 ns Max, (5µs<math>\lt; PW < 0.1s</math>)
Power Handling:.....	Operating..... +20 dBm CW/Peak Max
.....	Survival..... +30 dBm CW/AVG Max
Connectors (RF):.....	SMA (f), Removable
Connector (Supply & Controls):.....	Solder Pins
Impedance:.....	50 Ohms Nominal
Quality:.....	Best-Commercial-Grade

Environmental Ratings:

Temperature:.....	{Operating: -40°C to +85°C} & {Storage: -50°C to +100°C}
Humidity:.....	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:.....	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:.....	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:.....	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:.....	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Outline

("A" = 0.515" [13.1mm] <> Tolerances: ±0.015" [0.38mm] <> Weight = 1.2 oz [34g])

