
LPA7-900L/938


COBHAM

Low Profile Antenna

The most important thing we build is trust

Designed for Security Applications
Suitable for Multiple Applications
Left Hand Circular Polarised
Low Profile





Elevation Pattern

TOP VIEW 50 0.79	92.72 [3.65]
1	224.20[8.83]
300 [11.81]	SMA(F) CONNECTOR - SMA(F) CONNECTOR
BASE VIEW GA: 0938	MOUNTED VIA 4 OFF

ELECTRICAL	
Frequency	870 - 960 GHz
Gain	7 dBiC Nom
Polarisation	Left Hand Circular
Beamwidth	80° (Az) x 80° (EI)
Axial Ratio	3 dB Typ
VSWR	1.5:1
Power Rating	10 W
Front to Back	20 dB
MECHANICAL	
Standard Finish	Gloss White
Mass	0.75 Kg (1.65 lbs)
Temperature	-20° to +50°C
Wind Loading	11.9 Kg (26.2 lbs) @ 100mph
MOUNTING OPTIONS	
Kits Available	N/A
See separate data sheet	:S

ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

Issued 040310

For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0) 1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com