

SPECIFICATION SHEET
JFW MODEL 50KFA-008
FIXED ATTENUATOR KIT

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Description	Kit of fixed attenuators supplied together in a case
Frequency Range	DC-18 GHz
Impedance	50 Ohms nominal
RF Connectors	N male/female
RF Input Power	2 Watts average @ +25°C Derate to 0.5 Watts @ +125°C
Parts Included	(1 piece) 3dB fixed attenuator, N male/female (1 piece) 6dB fixed attenuator, N male/female (1 piece) 10dB fixed attenuator, N male/female (1 piece) 20dB fixed attenuator, N male/female
Model Numbers for Each Individual Part	50HF-003 N (3dB Fixed Attenuator, N male/female) 50HF-006 N (6dB Fixed Attenuator, N male/female) 50HF-010 N (10dB Fixed Attenuator, N male/female) 50HF-020 N (20dB Fixed Attenuator, N male/female)
Calibration Frequencies	Each fixed attenuator has its attenuation recorded at each of the following frequencies: DC, 4 GHz, 8GHz, 12.4 GHz, 18GHz

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	09/24/2014		TRS 09/24/2014				