Low Pass Filter

VLP-20

50 Ω DC to 1700 MHz

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
BF Power Input*	14W max_at 25°C

^{*} Passband rating, derate linearly to 0.4xPmax at 100°C ambient. Permanent damage may occur if any of these limits are exceeded.

Features

- rugged unibody construction
- low insertion loss passband, less than 1 dB typ.
- excellent power handling, 14W
- low cost



CASE STYLE: FF704

Connectors	Model	Price	Qty.
SMA	VLP-20	\$24.95 ea.	(1-9)


Applications

- harmonic rejection
- transmitters/receivers
- lab use

Electrical Specifications (T_{AMB}=25°C)

PASSBAND (MHz)	fco, MHz Nom.	STOP BAND (MHz)			VSWR (:1)
(loss < 1 dB)	(loss 3 dB)				Passband
Тур.	Тур.	(loss > 20 dB)	(loss > 40 dB)	fr20 dB Typ.	Тур.
DC-1700	1980	2700	3300-3750	7200	1.1


Outline Drawing




Outline Dimensions (inch)

wt	Ε	D	В
grams	.312	1.43	.410
10.0	7.02	36 32	10 /1

typical frequency response




electrical schematic



Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)	
1.00	0.05	1.01	
1000.00	0.45	1.18	
1700.00	0.80	1.13	
1980.00	2.56	2.78	
2700.00	24.06	35.85	
3300.00	45.92	38.05	
3880.00	42.96	36.25	
5000.00	36.56	43.07	
7200.00	24.22	24.89	
9000.00	7.43	5.58	







For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com