

# C18ST

## CLIPPED SINE WAVE SURFACE MOUNT TCXO

### FEATURES

- Metal SMD case
- Wide frequency range
- Adjustable Frequency
- Applications: Base Stations, Test equipment, ...

18.3 x 11.7 x 4.5 mm



Item	Specification						
Frequency Range	1.0 MHz to 125.0 MHz						
Output Logic	Clipped Sine Wave						
Supply Voltage V <sub>dd</sub> (see options)	+3.3 V ±5%		+5.0 V ±5%				
Supply Current I <sub>dd</sub>	10 mA max		15 mA max				
Frequency Tolerance	±1.0 ppm max. at 25°C ±2°C (one hour after reflow)						
Frequency Stability vs Temperature ( see options )		±0.5 ppm	±1.0 ppm	±1.5 ppm	±2.0 ppm	±2.5 ppm	±3.0 ppm
	0° to +50°C	o	o	o	o	o	o
	-10° to +60°C	◇	o	o	o	o	o
	-20° to +70°C	x	o	o	o	o	o
	-30° to +75°C	x	◇	o	o	o	o
	-30° to +85°C	x	◇	◇	o	o	o
	-40° to +85°C	x	◇	◇	o	o	o
o = available		◇ = please contact us			x = not available		
Frequency Stability vs Aging	±1.0 ppm max. per year at 25°C						
Frequency Stability vs Voltage Change	±0.2 ppm max., for a ±5% input voltage change						
Frequency Stability vs Load Change	±0.2 ppm max., for a ±10% load condition change						
Output Level	≥0.8 V p-p						
Output Load	10 kΩ // 10 pF						
Start-up Time	3 ms max.						
Phase noise	Offset / dBc / Hz	10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	
	(typical)						
	10.000 MHz	-95 dBc / Hz	-130 dBc / Hz	-140 dBc / Hz	-145 dBc / Hz	-150 dBc / Hz	
38.880 MHz	-85 dBc / Hz	-110 dBc / Hz	-140 dBc / Hz	-150 dBc / Hz	-150 dBc / Hz		
Mechanical Frequency Tuning ( see options )	±3.0 ppm min. tuning						
Packing Unit	800 pcs / reel						
Soldering Condition	260°C, 10 sec x2 max						

Customer specifications on request


## OPTIONS & ORDERING INFORMATION

### C18ST

.....	.....	- .....	.....	.....	..... MHz	.....
Supply Voltage	Operating Temp. *	Temperature Stability *	Tri-state Function	Package type	Frequency in MHz	Mechanical Tuning
33 = +3.3V	C = 0° / +50°C	0.5 = ±0.5 ppm	F = No Tri-state	4P = 4-pad version	Please specify the frequency in MHz	Blanc = No trimmer
50 = +5.0V	D = -10° / +60°C	1.0 = ±1.0 ppm				-T = Trimmer option
	F = -20° / +70°C	1.5 = ±1.5 ppm				
	G = -30° / +75°C	2.0 = ±2.0 ppm				
	H = -30° / +85°C	2.5 = ±2.5 ppm				
	K = -40° / +85°C	3.0 = ±3.0 ppm				

(\*) Note : Not all combinations are possible, please consult us.

# OUTLINE DIMENSIONS



**Pin Connections**

#1 : NC

#2 : GND

#3: Output

#4 : Vdd