


PIN	CONNECTION
1	Freq adjustment
7	Ground
8	Output
14	Supply

Features

- **Compact 14-pin DIL package (SMD optional)**
- **3.3V supply voltage**
- **HCMOS compatible output**
- **Very fast warmup**
- **Low power consumption**
- **Wide temperature range available**

Specifications

Parameters	Product MCOCXOW	Option Codes
Frequency range: 10.0kHz ~ 54.0MHz	■	
Frequency stability: ±0.7ppm max first year ±4ppm max in 10 years ±0.1ppm over V_{DD} ±0.15V ±0.01ppm over 10% change in load	■ ■ ■ ■	
Short term stability: 5×10^{-10} , 0.1 to 30s 5×10^{-11} over 1s typ	■ ■	
Temperature stability: ±0.2ppm max, 0 to +60°C ±0.075ppm max, 0 to +60°C ±0.3ppm max, -20 to +70°C ±0.15ppm max, -20 to +70°C ±0.5ppm max, -40 to +85°C ±0.25ppm max, -40 to +85°C	□ □ □ □ □ □	A TA B TB C TC
Operable temperature range: -40 to +85°C	■	
Storage temperature range: -65 to +125°C	■	
Output waveform: HCMOS compatible '0' = +0.4V max, '1' = V_{DD} - 0.5V min 40:60 max	■ ■ ■	
Rise / fall times: 7ns / 7ns max	■	
Frequency adjustment: Control voltage (pin 1) ±4ppm min, 0V ~ 3.3V Variable resistor (pins 1 to 7) ±4ppm min, 0 ~ 10kΩ	□ □	V3 R1
Supply voltage (V_{DD}): +3.3V (±0.15V)	■	
Input current: 110mA max @ +30°C 170mA max @ -20°C	■ ■	
Warm up: within spec after 60s @ 0°C current 250mA max during 30s	■ ■	
Phase noise (typ @ 10MHz): -100dBc/Hz @ 10Hz -130dBc/Hz @ 100Hz -140dBc/Hz @ 1kHz -145dBc/Hz @ 10kHz	■ ■ ■ ■	
Shock & vibration: 2,000G, 0.3ms ½-sine 10.0 ~ 2,000Hz, 10G	■ ■	
Package: Through hole 14 pin DIL 25x22mm SMD carrier PCB Formed leads SMD	■ □ □	D1 D2

■ Standard. □ Optional - Please specify required code(s) when ordering

Ordering Information

Product name + option codes + frequency


eg: **MCOCXOWT-AR1 12.80MHz**

MCOCXOW-BV3 16.3840MHz


Option code X (eg MCOCXOW/X) denotes a custom spec.

♦ Product is NOT designed to withstand 260°C reflow processing

Option D1



Option D2



Soldering Profile

