

**SPECIFICATION SHEET**

**JFW MODEL 75S-364**

**1P8T SELF TERMINATING SOLID STATE RF SWITCH**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

Frequency Range	400-2200 MHz
Configuration	1P8T Self Terminating
Impedance	75 Ohms nominal
VSWR	1.3:1 typical 1.5:1 maximum
Insertion Loss	2.5 dB typical 3.0 dB maximum
Isolation	75 dB typical 65 dB minimum
Switching Speed	10 microseconds (50% TTL to 10% or 90% RF)
RF Input Power	+30 dBm average
Control Logic (8 Lines)	TTL "Low" (0-0.8V) for OFF and internally terminated in 75 Ohms  TTL "High" (2.0-5.0V) for ON [i.e. C1 High for J1-J9 (common)]
DC Supply	+12 Vdc @ 200 mA nominal
RF Connector	F female
Operating Temperature Range	0°C to +70°C
Storage Temperature Range	-55°C to +90°C
Physical Size	See outline drawing 092-6967

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	12/20/2013		BAC 12/20/2013				