


WR187 WAVEGUIDE 1000W HIGH POWER TERMINATION - RFWT187H

1.0 Mechanical Specifications	
1.1	Waveguide type Rectangular Waveguide WR187
1.2	Flange type CPRF, COVER
1.3	Flange Holes Through
1.4	Basis-material Alloyed Cuprum
1.5	Internal Body Finish Silver Plated chromate or conversion
1.6	External Body Finish Body painted with gray/black epoxy enamel

2.0 Environment specifications		
2.1	Operation Temp.	-40°C~+85°C
2.2	Storage Temp.	-50°C~+125°C
2.3	Altitude	45000 ft
2.4	Vibration	10g rms (15 degree 2KHz)
2.5	Humidity	100% RH at 35c, 95%RH at 40 deg c
2.6	Shock	20G for 11msc

3.0 Electrical Specifications		
3.1	Frequency Range	3.95-5.85GHz
3.2	Average Power	1000W (CW)
3.3	VSWR	1.15:1 (max)

PAGE 1 OF 1		DATE	Jun 21 st 2006
 RFWT187H WAVEGUIDE TERMINATION		DESIGN	RFPC
		RF-LAMBDA	RFPC
		CAD MODEL REVISION	11
		ASSEMBLY REVISION	V55DS
www.rflambda.com		ASSEMBLY NAME	RFLVR05
RF-LAMBDA		DRAWING NUMBER	D05-1
SIZE	LT	SHEETS	1 OF 1