

OUTPUTS

Output	Frequency	Level (into 50Ω)
A	10 MHz	+13 ±2 dBm
B	600 MHz	+13 ±2 dBm

STABILITY

Aging

- 1 x 10⁻⁷ first year after 30 days operating, typical
- 5 x 10⁻⁸ second year, typical
- 3 x 10⁻⁸ per year thereafter, typical

Phase Noise L(f), dBc/Hz, typical

	10 MHz	600 MHz
10 Hz	-140	-103
100 Hz	-160	-121
300 Hz	-165	-126
1 kHz	-172	-139
10 kHz	-174	-156
100 kHz	-175	-158

Temperature Stability

±5 x 10⁻⁹, 0 to +50°C (Ref. +25°C)

Harmonics

≤ -25 dBc

Sub-Harmonics

≤ -60 dBc

PLL Reference Products

≤ -60 dBc

Spurious

≤ -80 dBc, excluding power supply line related spurs

Phase Lock Alarm

TTL
 Locked: +3.5 VDC to +5.2 VDC (Hi)
 Out-of-Lock: +0.8 VDC max (Lo)

Phase Lock Voltage Monitor

Voltage monitor pin supplied

MECHANICAL

Dimensions

6.51 x 4 x 1"

Connectors

RF Outputs: SMA(f)
 Power, Monitoring: Feed Thru Terminals
 GND: Ground Turret

Packaging

Nickel-plated machined aluminum housing – J2PMX

Mounting

Threaded inserts on base, #2-56, 11 places

POWER REQUIREMENTS

Warm-Up Power

≤ 19 Watts for 5 minutes

Total Power

≤ 12 Watts at +25°C

Supply Voltage

+15 VDC ±5%

ADJUSTMENT

Mechanical Tuning (Internal 10 MHz)

±1 x 10⁻⁶

Loop BW (Internal 100 MHz PLL)

Target Bandwidth: ~300 Hz
 Type 2 Loop

CRYSTAL

Type

10 MHz SC-cut
 100 MHz SC-cut (x6)

ENVIRONMENT

Operating Temperature

0 to +50°C

Storage Temperature

-50 to +85°C

OTHER

Label


Use conventional label with the following information:
 501-25780 (Current Rev.)
 10M/600M MXO-PLMX
 +15 VDC
 Serial # - Date Code
 (Mark connectors with function)

Test Data

- Output Level
- Phase Noise
- Temperature Stability
- Harmonics, Subs, Products, Spurs
- Power – Warm-up and Total

REV	DATE	REVISION RECORD	DWN	AUTH
-	07-26-13	Initial Release	PAC	

J2PMX MXO Connections	
Connector	Function
1	Supply Voltage
2	Ground, Case
4	RF Output B
5	Phase Lock Voltage
6	Phase Lock Alarm
8	RF Output A



Wenzel Associates, Inc.
 Austin, Texas

Title:
10 & 600 MHz Multiplied Crystal Oscillator (MXO-PLMX)

P/N: 501-25780	Rev: -	Date: 07-26-13	Drawn:	Ref:
--------------------------	-----------	--------------------------	--------	------

Tolerances: (except as noted) Dimensions are in inches	0.XX Dec: ±0.030"	0.XXX Dec: ±0.010"	FSCM: 62821	Page 1 of 1
--	-----------------------------	------------------------------	-----------------------	-------------