

Panel Antenna Operates From 2.4 GHz to 2.5 GHz With a Nominal 19 dBi Gain SMA Female Input Connector



TECHNICAL DATA SHEET

PE51049

Panel Antenna Operates From 2.4 GHz to 2.5 GHz With a Nominal 19 dBi Gain SMA Female Input Connector

Configuration

Design Panel Frequency Range, GHz 2.4 to 2.5

Polarization Vertical or Horizontal

Interface 1 SMA Female

Electrical Specifications

Impedance, Ohms50Nominal Gain, dBi19Maximum Input Power, Watts6Maximum Input VSWR1.7:1

Mechanical Specifications

Temperature

Operating Range, deg C -40 to +60

Size

 Length, in [mm]
 14.6 [370.84]

 Width, in [mm]
 14.6 [370.84]

 Height, in [mm]
 1.57 [39.88]

 Weight, lbs [Kg]
 4.4 [2]

 Wind Loading, MPH [KPH]
 130 [209.21]

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

2 Dimensional OML Drawing PE51049

Notes: Values at 25 °C, sea level

Panel Antenna Operates From 2.4 GHz to 2.5 GHz With a Nominal 19 dBi Gain SMA Female Input Connector from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Panel Antenna Operates From 2.4 GHz to 2.5 GHz With a Nominal 19 dBi Gain SMA Female Input Connector PE51049

URL: http://www.pasternack.com/panel-antenna-371mm-sq-x-40mm-sma-female-19-dbi-pe51049-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE51049 CAD DrawingPanel Antenna Operates From 2.4 GHz to 2.5 GHz With a

