

**SPECIFICATION SHEET**  
**JFW MODEL 75DR-018**  
**DUAL ROTARY ATTENUATOR**

JFW Industries, Inc.  
 Phone: 317-887-1340  
 sales@jfwindustries.com  
 www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-30 dB in 1 dB steps
VSWR	1.4:1 maximum DC-500 MHz 1.5:1 maximum 500-1000 MHz
Insertion Loss	0.5 dB maximum
Attenuation Accuracy	± 0.4 dB (1 dB steps) ± 0.5 dB (10 dB steps)
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC or F female
Operating Temperature Range	-20°C to +85°C
Knob/Panel Mounting Drawing	092-8435-02
Outline Drawing	092-2135 (75DR-018 BNC)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
4524	03/15/2004	B	CLV 03/15/2004	22562	02/25/2013	D	TRS 02/25/2013
9999	05/15/2003	A	BAC 03/15/2004	23479	11/26/2013	E	TRS 11/27/2013
20324	07/13/2011	C	TRS 07/13/2011	25776	09/28/2015	F	TRS 09/29/2015