



Transfer Electromechanical Relay Switch DC to 12.4 GHz, N, 160 Watts, 12V Control with Latching

TECHNICAL DATA SHEET

PE71S6178

The PE71S6178 is a Transfer Switch that operates from DC to 12.4 GHz. The switch has a Latching actuator and 1M life cycles. The switch has an operating voltage of +12 Volts.

Features

- Transfer Switch
- DC to 12.4 GHz Operating Frequency Range
- 1 M Cycles min
- Latching Switch

Applications

- Test & Measurement
- Communications System
- Instrumentation

Electrical Specifications

Frequency Range	DC to 12.4 GHz
Impedance	50 Ohms
Actuator	Latching
Actuating Current	320 mA
Control Voltage	12 Volts
RF Input Power (Max CW)	160 Watts

RF Characteristic

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Frequency Range	DC to 4	4 to 8	8 to 12.4			GHz
VSWR, Max	1.2:1	1.3:1	1.45:1			
Insertion Loss, Max	0.2	0.3	0.4			dB
Isolation, Min	80	70	60			dB

Mechanical Specifications

Connector Type	N Female
Operating Life	1,000,000
Terminals	Solder Pins
Switching Time (nominal voltage, 25°C)	20 ms Max

Environmental Specifications

Temperature	
Operating Range	-25 to +65 deg C
Environment	Designed to Meet MIL-DTL-3928

Compliance Certifications (visit www.Pasternack.com for current document)

Not RoHS Compliant

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Transfer Electromechanical Relay Switch DC to 12.4 GHz, N, 160 Watts, 12V Control with Latching PE71S6178](#)



Transfer Electromechanical Relay Switch DC to
12.4 GHz, N, 160 Watts, 12V Control with Latching

TECHNICAL DATA SHEET

PE71S6178

Plotted and Other Data

Notes:

- Values at +25 °C, sea level
- ESD Sensitive Material, Transport material in Approved ESD bags. Handle only in approved ESD Workstation.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Transfer Electromechanical Relay Switch DC to 12.4 GHz, N, 160 Watts, 12V Control with Latching PE71S6178](#)





Transfer Electromechanical Relay Switch DC to 12.4 GHz, N, 160 Watts, 12V Control with Latching

TECHNICAL DATA SHEET

PE71S6178

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Transfer Electromechanical Relay Switch DC to 12.4 GHz, N, 160 Watts, 12V Control with Latching PE71S6178](#)



PE71S6178 CAD Drawing

Transfer Electromechanical Relay Switch DC to 12.4 GHz,
N, 160 Watts, 12V Control with Latching



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ARE:		ANGLES
DECIMALS	.XX ± .03 (0.76)	±1°
FRACTIONS	.XXX ± .010 (0.254)	FRACTIONS
		±1/16
HOLE DIAMETER	TOLERANCE	
.0135 TO .125 (0.343 TO 3.175)	+ .004 TO -.001 (+0.102 TO -0.025)	
.126 TO .250 (3.200 TO 6.350)	+ .005 TO -.001 (+0.127 TO -0.025)	
.251 TO .500 (6.375 TO 12.700)	+ .006 TO -.001 (+0.152 TO -0.025)	
.501 TO .750 (12.725 TO 19.050)	+ .008 TO -.001 (+0.203 TO -0.025)	
.751 TO 1.000 (19.075 TO 25.400)	+ .010 TO -.001 (+0.254 TO -0.025)	
1.001 TO 2.000 (25.425 TO 50.800)	+ .012 TO -.001 (+0.305 TO -0.025)	

* THESE DIMENSIONS AND TOLERANCES SUPERSEDE NOTE #1 ON TITLE BLOCK.



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE71S6178

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

FSCM NO. 53919

CAD FILE 042715


SCALE N/A

SIZE A

2233

PE71S6178 CAD Drawing

Transfer Electromechanical Relay Switch DC to 12.4 GHz,
N, 160 Watts, 12V Control with Latching



SCHEMATIC LATCHING SHOWN IN POSITION 1

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE71S6178

PE PASTERNAK
 THE ENGINEER'S RF SOURCE
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
 Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919

CAD FILE 042715

SCALE N/A

SIZE A

2233