

RF POWER AMPLIFIERS MODEL 8000-002



MODEL 8000-002

- IEC/EN 61000-4-3, 20 V/m
- High Reliability GaAs Design
- Excellent Performance and Efficiency
- Safety Interlock

ETS-Lindgren's Model 8000-002

RF Power Amplifier is a 275W power amplifier, designed primarily for EMC applications that include IEC/EN 61000-4-3, 20 V/m requirements. Utilizing GaAs technology, this RF amplifier provides higher linearity, rugged design and better efficiency performance versus silicon-based amplifiers.

The 8000-002 provides very low distortion and tolerance for 100% mismatch.

Technical Specifications

Electrical	
Frequency Range	80 MHz to 1 GHz
Nominal Output Power	275W
Gain Variation	± 3 dB
Harmonics	-20 dBc Maximum
Output Impedance	50 Ω
Input VSWR	2:1 Maximum
AC Supply	220 to 240 VAC, Single Phase
Supply Frequency Range	50/60 Hz
Line Power	< 2 kVA
Mechanical	
Remote Interface	GPIB
RF Connectors	Type N
Physical	
Dimensions	19 in, 6U Case, 550 mm (21.7 in) Deep
Weight	25.0 kg (55.1 lb)
Case Style (Standard)	Rack Mount with Rear Panel Connectors
Case Style (Optional)	Bench Mount, Front Panel Connectors

Typical Output Power at 1 dB Compression

