

SPECIFICATION SHEET

JFW MODEL 50S-1783

1P4T SELF TERMINATING SOLID STATE RF SWITCH

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	0.5-18 GHz
Configuration	1P4T Self Terminating
Impedance	50 Ohms nominal
VSWR	1.4:1 typical 0.5-4GHz 1.7:1 typical 4-18GHz 2.0:1 maximum 0.5-18GHz
Insertion Loss	2.0 dB typical 0.5-8GHz 3.0 dB typical 8-18GHz 3.5 dB maximum 0.5-18GHz
Isolation	80 dB typical 0.5-8GHz 70 dB typical 8-18GHz 65 dB minimum 0.5-18GHz
Switching Speed (50% TTL to 10% or 90% RF)	100 nanoseconds maximum 50 nanoseconds typical
RF Input Power	+27 dBm maximum
3rd Order Intercept Point	+45dBm minimum
Control Logic (4 Lines) (1 line per port)	TTL "Low" (0-0.8V) for OFF and Terminated TTL "High" (2.0-5.0V) for Insertion Loss (only one port active at a time)
DC Supplies	+5 ±0.3 Vdc @ 160 mA nominal and -12 to -15 Vdc @ 40 mA nominal
DC Connector	Solder Terminals
RF Connector	SMA female
Operating Temperature Range	-55°C to +85°C
Storage Temperature Range	-65°C to +125°C
Weight	36 grams nominal
Physical Size	See outline drawing 092-8413

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	09/14/2015		BAC 09/14/2015				
26495	03/30/2016	A	BAC 03/30/2016				
26628	05/03/2016	B	BAC 05/03/2016				