

**SPECIFICATION SHEET**  
**JFW MODEL 75DR-009**  
**DUAL ROTARY ATTENUATOR**

JFW Industries, Inc.  
 Phone: 317-887-1340  
 sales@jfwindustries.com  
 www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-70 dB in 1 dB steps
VSWR	1.4:1 maximum
Insertion Loss	0.75 dB maximum
Attenuation Accuracy	± 0.5 dB or 3% (whichever is greater)
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC, F, or N female
Operating Temperature Range	-20°C to +85°C
Knob/Panel Mounting Drawing	092-8435-02
Outline Drawings	092-327-04 (75DR-009 N) 092-1513-04 (75DR-009 BNC) 092-7445-01 (75DR-009 F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
2384	05/22/2000	A		21892	09/06/2012	D	BAC 09/06/2012
9999	05/15/2003	B	TRS 04/28/2004	22778	04/19/2013	E	TRS 04/19/2013
17253	05/26/2009	C	TRS 05/27/2009	25776	09/28/2015	F	TRS 09/29/2015