



# 50 Ohm 8 Way SMA Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts

# **TECHNICAL DATA SHEET**

PE2091

## 50 Ohm 8 Way SMA Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts

# Configuration

Input Connector SMA Female
Input Connector Specification MIL-STD-348
Output Connectors SMA Female
Output Connectors Specification MIL-STD-348
Frequency Range, GHz 0.69 to 2.7
Design Wilkinson
Number of Output Ports 8
Housing Material and Plating Aluminum

## **Electrical Specifications**

 Frequency Range, GHz
 0.69 to 2.7

 Impedance, Ohms
 50

 Maximum Insertion Loss, dB
 1.2

 Maximum Input Power, Watts
 10

 Maximum Input VSWR
 1.4:1

 Minimum Isolation, dB
 20

 Phase Balance, Degrees
 ± 8

 Flatness, dB
 0.5

# **Mechanical Specifications**

#### **Temperature**

Operating Range, deg C -55 to +85

#### Size

 Length, in [mm]
 4.7 [119.38]

 Width, in [mm]
 8.3 [210.82]

 Height, in [mm]
 0.8 [20.32]

 Color
 Blue

# **Input Connector**

Contact Material and Plating

Connector Material and Plating

Beryllium Copper, Gold

Passivated Stainless Steel

Body Material and Plating

Passivated Stainless Steel

### **Output Connectors**

Contact Material and Plating

Connector Material and Plating

Beryllium Copper, Gold

Passivated Stainless Steel

Body Material and Plating

Passivated Stainless Steel

Passivated Stainless Steel

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm 8 Way SMA Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts PE2091

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





# 50 Ohm 8 Way SMA Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts

# **TECHNICAL DATA SHEET**

PE2091

Compliance Certifications (visit www.Pasternack.com for current document)

#### **Plotted and Other Data**

Notes:

Values at 25 °C, sea level

50 Ohm 8 Way SMA Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm 8 Way SMA Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts PE2091

URL: http://www.pasternack.com/8-way-sma-wilkinson-power-divider-690-mhz-2.7-ghz-10-watts-pe2091-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



