

Coaxial Bandpass Filter

ZFBP-2400+

50Ω 2300 to 2500 MHz

The Big Deal

- Narrow bandwidth
- Good VSWR, 1.3:1 typical
- High rejection, 50 dB typical
- Flat group delay, 0.3 ns typical
- High power, 8.5W



CASE STYLE: H16

Product Overview

ZFBP-2400+ is a 50Ω narrow band filter built into a shielded (size: 1.25" x 1.25" x 0.75") case. Covering a bandwidth of 2400 MHz ± 100 MHz, this filter offers good matching in the passband and high rejection in the stopband. Power handling capacity is as high as 8.5W at 25°C.

Key Features

Feature	Advantages
Narrow bandwidth (Fractional bandwidth of 8.3%)	Suitable for Narrow bandwidth applications like Wireless Communication Service and ISM.
Good VSWR, 1.3:1 typical	The model has good return loss for a narrow bandwidth which provides good matching when used with other devices.
High rejection (50 dB typical on lower side band and > 35 dB rejection till 6000 MHz on upper side band)	This enables the filter to attenuate sub harmonics and spurious signals.
Flat group delay characteristics (0.3 ns typical)	The model has a group delay flatness of 0.3 ns which helps in reducing the signal distortion.
High power (8.5W)	Suitable for base station and long-haul applications and test labs.



For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine  Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Bandpass Filter

ZFBP-2400+

50Ω 2300 to 2500 MHz



CASE STYLE: H16

Connectors	Model	Price	Qty.
SMA-Female	ZFBP-2400-S+	\$49.95 ea.	(1-9)
BRACKET (OPTION "B")		\$5.00 ea.	(1-9)

Features

- High rejection, 50 dB typical
- Flat group delay over passband, 0.3 ns typical
- Good VSWR, 1.3:1 typical in passband
- Rugged shielded case

Applications

- Harmonic rejection
- Transmitters / receivers
- Lab use

Electrical Specifications at 25°C


Parameter	F#	Frequency (MHz)	Min.	Typ.	Max.	Unit	
Pass Band	Center Frequency	—	—	2400	—	MHz	
	Insertion Loss	F1-F2	2300 - 2500	—	2.2	3.5	dB
Stop Band, Lower	VSWR	F1-F2	2300 - 2500	—	1.3	1.65	:1
	Insertion Loss	DC-F3	DC - 1800	20	30	—	dB
Stop Band, Upper	VSWR	DC-F3	DC - 1800	—	50	—	:1
	Insertion Loss	F4-F5	2800 - 6000	20	28	—	dB
Stop Band, Upper	VSWR	F4-F5	2800 - 6000	—	16	—	:1

Maximum Ratings


Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input*	8.5W max. at 25°C

* Derate linearly to 4W at 100°C ambient.
Permanent damage may occur if any of these limits are exceeded.

Functional Schematic



Typical Frequency Response







Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)	Frequency (MHz)	Group Delay (nsec)
0.5	95.43	1737.18	2300.0	3.48
500.0	55.03	144.77	2310.0	3.44
1100.0	46.14	115.81	2320.0	3.40
1800.0	32.22	56.04	2330.0	3.38
2070.0	16.34	18.70	2340.0	3.36
2150.0	8.89	7.94	2350.0	3.35
2200.0	4.52	3.42	2360.0	3.34
2270.0	1.86	1.19	2370.0	3.34
2300.0	1.72	1.07	2380.0	3.35
2400.0	1.92	1.27	2390.0	3.35
2500.0	2.19	1.26	2400.0	3.37
2600.0	3.40	1.14	2410.0	3.38
2620.0	5.02	1.52	2420.0	3.39
2660.0	14.64	4.39	2430.0	3.41
2800.0	32.28	15.81	2440.0	3.43
3050.0	47.48	32.79	2450.0	3.45
3300.0	49.58	44.55	2460.0	3.48
4800.0	36.24	46.96	2470.0	3.50
5600.0	32.22	36.20	2480.0	3.54
6000.0	29.22	24.83	2500.0	3.64

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.



For detailed performance specs & shipping online see web site


P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Coaxial Connections

INPUT	1 (SMA female)
OUTPUT	2 (SMA female)

Outline Drawing



Outline Dimensions (inch mm)

A	B	C	D	E	F	G	H
1.25	1.25	.75	.63	.38	1.000	.125	1.000
31.75	31.75	19.05	16.00	9.65	25.40	3.18	25.40
J	K	L	M	N	P	Q	wt
--	--	.125	1.688	2.18	.750	.06	grams
--	--	3.18	42.88	55.37	19.05	1.52	70.0