

<b>Flexiguide</b>			<b>Frequency</b>	<b>Max Power</b>	<b>CW Power</b>	<b>Insertion Loss</b>	<b>Return Loss (dB)</b>				
<b>WG</b>	<b>WR</b>	<b>R</b>	<b>GHz</b>	<b>MW</b>	<b>kW</b>	<b>dB/m</b>	<b>300 mm</b>	<b>600 mm</b>	<b>1000 mm</b>	<b>1500 mm</b>	<b>2000 mm</b>
10	284	32	2.60 - 3.95	2.2	4	0.11	31.4	30.0	29.5	28.5	27.5
11A	229	40	3.30 - 4.90	1.8	4	0.15	31.0	29.5	28.8	27.8	26.8
12	187	48	3.95 - 5.85	1.4	3	0.16	31.0	28.8	28.3	27.3	26.3
13	159	58	4.90 - 7.05	0.6	2.5	0.18	31.0	28.3	27.8	26.8	25.8
14	137	70	5.85 - 8.20	0.56	2	0.28	30.2	27.8	27.3	26.3	25.3
15	112	84	7.05 - 10.00	0.33	1.5	0.30	30.2	27.3	27.1	26.1	25.1
16	90	100	8.20 - 12.40	0.22	1	0.40	30.2	27.1	27.0	26.0	25.0
17	75	120	10.00 - 15.00	0.18	0.75	0.50	29.4	27.0	26.4	25.4	24.4
18	62	140	12.40 - 18.00	0.12	0.4	0.80	29.4	26.4	26.0	25.0	24.0
19	51	180	15.00 - 22.00	0.085	0.2	1.00	26.4	25.0	24.5	23.5	22.5
20	42	220	17.70 - 26.50	0.045	0.1	1.20	23.0	22.1	21.1	20.1	19.1
21	34	260	22.00 - 33.00	0.031	0.085	1.50	22.1	21.0	20.0	19.0	18.0
22	28	320	26.50 - 40.00	0.022	0.075	2.00	21.0	17.7	17.1	16.1	15.1
23	22	400	33.00 - 50.00	N/A	N/A	2.50	20.0	16.5	16.0	15.0	14.0