

**SPECIFICATION SHEET**  
**JFW MODEL 50FHXC-XXX-40**  
**FIXED ATTENUATOR**

JFW Industries, Inc.  
 Phone: 317-887-1340  
 sales@jfwindustries.com  
 www.jfwindustries.com

Frequency Range DC-4000 MHz (1-30 dB)  
 DC-3000 MHz (31-60 dB)

Impedance 50 Ohms nominal

Attenuation Values 1-60 dB in any 1 dB increment  
 (XXX) insert value

VSWR (1-30 dB) 1.15:1 maximum DC-1000 MHz  
 1.35:1 maximum 1000-4000 MHz  
 (31-60 dB) 1.15:1 maximum DC-1000 MHz  
 1.35:1 maximum 1000-3000 MHz

Attenuation Accuracy (1-20 dB)  
 ± 0.25 dB DC-1000 MHz  
 ± 0.50 dB 1000-4000 MHz  
 (21-30 dB)  
 ± 0.50 dB DC-1000 MHz  
 ± 0.75 dB 1000-4000 MHz  
 (31-60 dB)  
 ± 2% DC-2000 MHz  
 ± 3% 2000-3000 MHz

RF Input Power 40 Watts average  
 Derate to 20 Watts @ +70°C

Peak Power 1000 Watts

RF Connector BNC, N, SMA, RPT, TNC, 4.1-9.5,  
 4.3-10.0 or 7/16  
 (RPT = reverse polarity TNC)

Operating Temperature Range -55°C to +100°C

Physical Size See outline drawing 092-6093

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	02/23/2009	O	SMR 02/23/2009	26024	12/14/2015	C	TRS 12/14/2015
23610	01/02/2014	A	BAC 01/02/2014				
26007	12/14/2015	B	CLK 12/14/2015				