

5

4

3

2

1


**PRODUCTION  
RELEASE**

NOTE:  
THIS DRAWING INCORPORATES  
THIRD ANGLE PROJECTION.  
INTERPRET IAW ANSI Y14.5-1992

REVISIONS

LTR	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	2/23/11	T. KUHN

INTERFACE IAW MIL-STD-348 FOR  
2.92mm (SMK) AND MATES WITH ALL  
SMA CONNECTORS AS WELL.



M07  
NOTES:

- MATERIAL:**  
HOUSING: STAINLESS STEEL IAW ASTM-A484 & ASTM-A582,  
ALLOY 303, COND A  
CONTACT: BERYLLIUM COPPER  
DIELECTRIC - HIGH TEMPERATURE PLASTIC BEAD
- FINISH:**  
HOUSING - PASSIVATED STAINLESS STEEL  
CONDUCTOR - GOLD PLATED IAW MIL-PRF-39012
- ELECTRICALS:**  
VSWR (MAX) DC-26.5 GHz 1.25 MAX.  
POWER (AVG. MAX.) @25°C SEE TABLE  
DERATES LINEARLY TO 10% @ +125°C  
OPERATING TEMPERATURE RANGE °C -55 to +125

ORDERING INFORMATION

4801-700X-02-26	POWER LEVEL
X = 0	0.5 WATT
X = 1	1 WATT
X = 2	2 WATT

4801-700X-02-26 NO CHAIN  
4801-700X-02-26-C 2" CHAIN ADDED

DRAWING PRACTICES PER ANSI-Y-14.5 MIL-STD-100 & 1000	UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES AND APPLY BEFORE/AFTER PROCESSING	TOLERANCES IN:
SURFACE ROUGHNESS #INCHES 63 ✓	DECIMALS INCH DIMI
FINISH	.X" .05" [1.3]
SEE NOTES	.XX" .030" [.76]
MATERIAL	.XXX" .02 [.51]
SEE NOTES	.XXXX" ANGLES
	UNLESS OTHERWISE NOTED DIAS CONCENTRIC <.003 T.I.R.

DRAWN T. KUHN	DATE 5/13/09
CHECKED	DATE
ENGINEER APPR. T. KUHN	DATE 5/13/09
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF XMA CORP. OR OMNI SPECTRA AND SHALL NOT BE REPRODUCED, COPIED NOR USED - IN WHOLE OR IN PART - AS A BASIS FOR THE MANUFACTURE OR SALE OF OTHER ITEMS WITHOUT THE EXPRESS WRITTEN PERMISSION OF XMA CORP.	

**XMA** Powered by:  
**Omni Spectra®**  
Phone: 603-222-2256 Fax: 603-222-2259  
150 Dow Street, Manchester, NH 03101

TITLE 2.92 mm MALE TERMINATION, DC-26.5 GHz			
SIZE B	CAGE CODE 3HT76	DRAWING NUMBER 4801-700X-02-26	
SCALE 6:1	PLATED AREA SQ. IN XXX	SHEET 1 OF 1	

5

4

3

2

1

BCSI