

DROP-IN ISOLATOR

FREQUENCY GHz	ISOLATION dB, MIN	INSERTION LOSS dB, MAX	VSWR MAX	POWER WATTS		MODEL#	DIMENSIONS IN INCHES
				FWD	REV		
1.400 - 1.600	18	0.400	1.300:1	50	10	2H3NC	0.750 x 0.750 x 0.300
1.625 - 1.660	20	0.300	1.200:1	80	70	2H4NHD	0.750 x 1.000 x 0.300
1.600 - 1.800	20	0.500	1.250:1	50	10	2H4NEW	0.750 x 0.750 x 0.300
1.700 - 1.900	20	0.500	1.250:1	50	10	2H4NBS	0.750 x 0.750 x 0.300
1.700 - 1.800	20	0.500	1.250:1	50	10	2H4NAU	0.750 x 0.750 x 0.300
1.840 - 1.870	22	0.300	1.200:1	125	70	2H4NGZ	0.750 x 1.000 x 0.300
1.930 - 1.990	22	0.300	1.200:1	65	65	2H4NGT	0.750 x 0.825 x 0.220
1.800 - 2.000	20	0.500	1.250:1	50	10	2H4NBI	0.750 x 0.750 x 0.300
1.900 - 2.100	20	0.300	1.250:1	50	10	2H4NBT	0.750 x 0.750 x 0.220
2.110 - 2.170	22	0.300	1.200:1	125	70	2H4NHA	0.750 x 1.000 x 0.300
2.100 - 2.200	20	0.300	1.180:1	125	125	2H4NHC	0.750 x 1.000 x 0.300
2.000 - 2.500	20	0.500	1.250:1	50	10	2H4NFW	0.875 x 0.875 x 0.345
2.500 - 2.700	20	0.400	1.200:1	100	70	2H4NFY	0.750 x 1.250 x 0.310
2.700 - 2.900	20	0.300	1.200:1	50	10	2H5NA	0.750 x 0.750 x 0.300
2.900 - 3.200	20	0.500	1.250:1	50	10	2H5NE	0.750 x 0.750 x 0.300
3.100 - 3.500	18	0.600	1.300:1	50	10	2H5NAV	0.500 x 0.500 x 0.180
3.200 - 3.600	20	0.500	1.200:1	50	10	2H5NAD	0.750 x 0.750 x 0.250
3.600 - 4.200	18	0.500	1.300:1	50	10	2H5NAC	0.500 x 0.500 x 0.180
4.200 - 4.400	20	0.400	1.250:1	50	10	2H6NA	0.500 x 0.500 x 0.210
4.400 - 5.000	18	0.400	1.300:1	50	10	2H6NW	0.500 x 0.500 x 0.180
5.000 - 6.000	20	0.500	1.200:1	50	10	2H6NU	0.500 x 0.500 x 0.180
6.000 - 7.000	19	0.500	1.200:1	50	10	2H7NBX	0.500 x 0.500 x 0.180
7.000 - 8.500	20	0.500	1.200:1	50	10	2H7NAD	0.500 x 0.500 x 0.180
5.800 - 6.400	20	0.500	1.250:1	50	10	2H7NBS	0.500 x 0.500 x 0.180
6.400 - 7.200	20	0.500	1.220:1	50	10	2H7NBH	0.500 x 0.500 x 0.180
9.000 - 10.000	20	0.050	1.500:1	50	10	2H8NAG	0.500 x 0.500 x 0.180
10.000 - 11.000	20	0.500	1.250:1	50	10	2H8NAR	0.500 x 0.500 x 0.180
10.950 - 12.750	21	0.500	1.250:1	50	10	2H8NR	0.500 x 0.500 x 0.180
13.750 - 14.500	20	0.500	1.250:1	50	10	2H9NAX	0.500 x 0.500 x 0.180
13.750 - 14.500	20	0.500	1.250:1	50	21	2H9NAV	0.500 x 0.750 x 0.180
14.500 - 15.500	20	0.500	1.250:1	10	1	2H9NAY	0.250 x 0.250 x 0.130



TYPICAL PACKAGE DIMENSIONS

