


Surface Mount

Diplexer

DPB6588-75+

75Ω DC to 1220 MHz
(DC-65, 88-1220 MHz)



CASE STYLE: PA2002

The Big Deal

- Low insertion loss, 1.2dB Typ.
- High rejection, > 45dB
- Very good return loss, 22dB Typ.
- 75Ω Impedance
- Used in DOCSIS 3.1 standard

Product Overview

DPB6588-75+ is a high performance diplexer with the lowpass port at DC-65 MHz and highpass port at 88-1220 MHz. Excellent return loss combined with high out of channel rejection makes it a ideal component in cable TV and multiband radio systems.

Key Features

Feature	Advantages
Low passband insertion loss	Passband insertion loss 1.2dB typical ensures low signal loss through both the channels.
Excellent Stopband rejection	Co-channel rejection of 45dB ensures unwanted spurious are eliminated.
Excellent return loss at DC-65 and 88-1220 MHz	This makes signal transmission with very less reflection and well-matched with the adjacent component used in the system.

Notes


- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Surface Mount Diplexer

DPB6588-75+

75Ω DC to 1220 MHz (DC-65, 88-1220 MHz)



CASE STYLE: PA2002

Maximum Ratings

Operating Temperature	-40° to 85°C
Storage Temperature	-55°C to 100°C
RF Power Input	27dBm Max.

Permanent damage may occur if any of these limits are exceeded. These ratings are not intended for continuous normal operation

Pin Connections

HIGH PASS PORT	7
LOW PASS PORT	9
COMMON PORT	18
GROUND	1-6,8,10-17,19,20

Features

- Low insertion loss
- 75Ω Impedance
- Excellent return loss
- High rejection

Applications

- Cable TV systems (DOCSIS 3.1 standard)
- Multiband radio systems

+RoHS Compliant
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Electrical Specifications at 25°C

Parameter	Port	Frequency (MHz)	Min.	Typ.	Max.	Unit	
Pass Band	Insertion Loss	Low Pass	DC-65	-	0.9	1.5	dB
		High Pass	88-1220	-	1.2	1.6	
	Return Loss	Low Pass	DC-65	18	22	-	dB
		High Pass	88-1220	17	22	-	
Common		DC-65	18	22	-		
Stop Band Isolation	Low Pass	88-900	45	50	-	dB	
	High Pass	900-1220	43	45	-		
		DC-65	45	50	-		

Typical Performance Data at 25°C

FREQUENCY (MHz)	INSERTION LOSS (dB)			RETURN LOSS (dB)	
	Low Pass Port	High Pass Port	Common Port	Low Pass Port	High Pass Port
1.0	0.04	85.70	51.54	51.03	0.03
10.0	0.08	75.18	34.87	34.81	0.01
50.0	0.30	79.72	28.11	27.57	0.25
60.0	0.50	71.47	35.00	38.45	0.45
65.0	0.71	72.36	29.02	27.15	0.59
70.0	1.13	46.18	28.91	37.15	0.77
74.0	2.87	32.11	9.96	9.24	1.03
75.0	4.28	26.87	7.10	6.07	1.16
76.0	6.45	20.73	5.18	3.87	1.36
78.0	13.24	10.96	4.02	1.70	2.37
79.5	20.35	6.32	5.25	1.12	4.27
80.0	23.05	5.24	6.05	1.01	5.22
81.5	31.33	3.12	9.48	0.81	8.99
85.0	45.19	1.54	21.56	0.61	22.52
88.0	56.57	1.20	31.45	0.53	40.52
100.0	73.85	0.78	32.40	0.42	26.41
250.0	63.55	0.43	31.93	0.32	24.72
300.0	62.79	0.43	53.49	0.30	26.76
500.0	58.93	0.46	22.84	0.26	21.95
900.0	54.17	0.56	19.64	0.37	21.78
1000.0	52.95	0.56	20.72	0.41	27.02
1220.0	49.63	0.61	21.03	0.53	25.18


Outline Drawing




Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K
1.181	1.181	.300	.197	.394	.591	.787	.984	.071	.079
30.00	30.00	7.62	5.00	10.00	15.00	20.00	25.00	1.80	2.00
L	M	N	P	Q	R	S	T	U	Wt.
.111	.394	.179	1.221	1.221	.079	.091	.280	.178	grams
2.82	10.00	4.54	31.01	31.01	2.01	2.31	7.11	4.52	3.8

Demo Board MCL P/N: TB-786+ Suggested PCB Layout (PL-435)








Functional Schematic



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp





Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

