

## Omni-Directional Antenna Operating From 58 GHz to 63 GHz With a Nominal 0 dBi Gain and WR-15 Waveguide Input



**PE-W15A001** 

### **TECHNICAL DATA SHEET**

Pasternack's PE-W15A001 is a vertically polarized WR-15 antenna operating between 58 GHz and 63 GHz and has a standard UG387/U flange. This omni-directional antenna has a 35 degree vertical beam width and a 360 degree horizontal gain variation. PE-W15A001 is ideal for short range wireless communications, indoor networks, high frequency applications and millimeter wave 60 GHz development systems. It is constructed with a brass waveguide and aluminum body.

#### Configuration

Design Frequency Range Polarization Interface 1 Interface 1 Specification Housing Material and Plating Fixed Waveguide 58 to 63 GHz Vertical WR-15 UG387/U Aluminum

#### Electrical Specifications (Values at 25°C, sea level)

Description	Minimum	Typical	Maximum	Units	
Gain Variation		3		dBi	
Horizontal 3dB Beam Width		360		Degrees	
Vertical 3dB Beam Width		35		Degrees	
Input Power	1			Watts	
chanical Specifications Radome Material		Rexolite			
Housing Material		Aluminum			
Size					
Length	1.78 in [45.21 mm]				
Width		4 in [101.6 mm]			
Connectors					
Description	Connector 1	Connecto	or 2 (	Connector 3	
Outer Conductor Material and Plating	Brass				
Body Material and Plating	Brass				

Compliance Certifications (visit www.Pasternack.com for current document) RoHS Compliant

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Omni-Directional Antenna Operating From 58 GHz to 63 GHz With a Nominal 0 dBi Gain and WR-15 Waveguide Input PE-W15A001

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com





Omni-Directional Antenna Operating From 58 GHz to 63 GHz With a Nominal 0 dBi Gain and WR-15 Waveguide Input




## **TECHNICAL DATA SHEET**

# PE-W15A001

### Plotted and Other Data

- Notes:
- Values at 25 °C, sea level

### **Outline Drawing**



Omni-Directional Antenna Operating From 58 GHz to 63 GHz With a Nominal 0 dBi Gain and WR-15 Waveguide Input from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Omni-Directional Antenna Operating From 58 GHz to 63 GHz With a Nominal 0 dBi Gain and WR-15 Waveguide Input PE-W15A001

URL: http://www.pasternack.com/omnidirectional-antenna-58-63-ghz-0-dbi-gain-wr-15-waveguide-pe-w15a001-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

