

SPECIFICATION SHEET

JFW MODEL 50R-043

ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-1000 MHz

Impedance 50 Ohms nominal

Attenuation Range 0-100 dB in 10 dB steps

VSWR 1.2:1 maximum

Insertion Loss 0.3 dB maximum

Attenuation Accuracy ± 0.5 dB or 2%
(whichever is greater)

RF Input Power 2 Watts average
1000 Watts peak

Direction of Rotation Attenuation increases in a Clockwise
direction

Indexing 30 degrees with stops at
Minimum and maximum

RF Connector BNC, N, SMA, or TNC

Operating Temperature Range -20°C to +85°C

Knob/Panel Mounting Drawing 092-8435-01

Physical Size 092-428-01 (50R-043 BNC)
092-428-02 (50R-043 BNC/SMA)
092-428-03 (50R-043 N)
092-428-04 (50R-043 N/SMA)
092-428-05 (50R-043 TNC)
092-428-06 (50R-043 TNC/SMA)
092-428-07 (50R-043 SMA)
092-428-08 (50R-043 N F/M)
092-428-09 (50R-043 N M/F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	04/21/2003	A	TRS 05/15/2007	18358	03/05/2010	D	TRS 03/05/2010
15177	01/14/2008	B	TRS 01/14/2008	19092	09/03/2010	E	TRS 09/03/2010
17378	07/02/2009	C	TRS 07/02/2009	25776	09/28/2015	F	TRS 09/29/2015