

SPECIFICATION SHEET

JFW MODEL 75R-057

ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-1 dB in 0.1 dB steps
VSWR	1.3:1 maximum DC-500 MHz 1.4:1 maximum 500-1000 MHz
Insertion Loss	0.8 dB maximum
Attenuation Accuracy	± 0.04 dB DC-500 MHz ± 0.08 dB 500-1000 MHz
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Counter-Clockwise direction
Indexing	30 degrees with stops at minimum and maximum
RF Connector	BNC or F female
Operating Temperature Range	-20°C to +85°C
Knob/Panel Mounting Drawing	092-8435-03
Outline Drawings	092-002-01 (75R-057 BNC) 092-002-02 (75R-057 F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	05/22/1995			17378	07/02/2009	C	TRS 07/02/2009
610	10/03/1996	A		22212	12/04/2012	D	TRS 12/04/2012
9999	05/19/2003	B	BAC 02/05/2004	25779	09/29/2015	E	TRS 09/29/2015