

**SPECIFICATION SHEET**

**JFW MODEL 50R-215**

**ROTARY ATTENUATOR**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

Frequency Range	DC-2200 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-1 dB in 0.1 dB steps
VSWR	1.2:1 maximum DC-1000 MHz 1.4:1 maximum 1000-2200 MHz
Insertion Loss	1 dB maximum
Attenuation Accuracy	± 0.05 dB
RF Input Power	2 Watts average
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC, SMA or TNC female
Operating Temperature Range	-20°C to +85°C
Knob/Panel Mounting Drawing	092-8435-01
Outline Drawings	092-039 (50R-215 SMA) 092-427 (50R-215 BNC)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	04/19/1993			25776	09/29/2015	C	TRS 09/29/2015
9999	04/30/2003	A	TRS 05/16/2007				
20829	11/01/2011	B	TRS 11/01/2011				