



ISSUE 1; September 2014 - RoHS 2011/65/EU

Description

- Temperature compensated, voltage controlled crystal oscillator in a ceramic package with a metal lid, not hermetically sealed

Frequency Parameters

- Frequency 13.0MHz to 52.0MHz
- Frequency Stability $\pm 1.00\text{ppm}$ to $\pm 2.00\text{ppm}$
- Ageing $\pm 1\text{ppm}$ max per year
- Load Variation (@ $\pm 10\%$): $\pm 0.1\text{ppm}$ max
- Supply Voltage Variation (@ $\pm 5\%$): $\pm 0.2\text{ppm}$ max

Electrical Parameters

- Supply Voltage 3.0V $\pm 5\%$

Frequency Adjustment

- Pulling $\pm 8\text{ppm}$ to $\pm 15\text{ppm}$
- Control Voltage $\pm 1.5\text{V}$ $\pm 1.5\text{V}$
- Slope: Positive

Operating Temperature Ranges

- 10 to 75°C
- 20 to 80°C
- 30 to 85°C

Output Details

- Output Compatibility Clipped Sine
- Drive Capability 10k Ω //10pF

Output Levels

- 0.8V pk-pk min

Noise Parameters

- Harmonics: -5dBc max


Environmental Parameters

- Storage Temperature Range: -40 to 85°C
- Drop: a test piece (100g) made of teflon is dropped 3 cycles (1 cycle: 6 directions) from a height of 150cm onto a hard board
- Vibration: 1.5mm amplitude, 10Hz-55Hz-10Hz, 1min in 3 mutually perpendicular planes, duration 2hrs each plane (total 6hrs)


Ordering Information

- Frequency*
Model*
Output
Frequency Stability*
Operating Temperature Range*
Supply Voltage
(*minimum required)
- Example
13.0MHz IQXT-171
Clipped Sine $\pm 2.0\text{ppm}$ -30 to 85C 3.0V

Outline (mm)



Test Circuit



Sales Office Contact Details:

UK: +44 (0)1460 270200

France: +33 (0)5 34 50 91 18

Email: info@iqdfrequencyproducts.com

Germany: +49 (0) 30 408 192 300

USA: +1 408.273.4530

Web: www.iqdfrequencyproducts.com



Compliance

- RoHS Status Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): 1

Packaging Details

- Pack Style: Reel Tape & reel in accordance with EIA-481-D
Pack Size: 4,000
- Pack Style: Bulk Loose in bulk pack
Pack Size: 100

Electrical Specification - maximum limiting values 3.0V ±5%

Frequency Min	Frequency Max	Temperature Range	Stability (min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
13.0MHz	52.0MHz	-10 to 75	±1.0	2	-	-
		-20 to 80	±1.0	2	-	-
		-30 to 85	±1.0	2	-	-

*This document was correct at the time of printing; please contact your local sales office for the latest version.
[Click to view latest version on our website.](#)*

Sales Office Contact Details:

UK: +44 (0)1460 270200

France: +33 (0)5 34 50 91 18

Email: info@iqdfrequencyproducts.com

Germany: +49 (0) 30 408 192 300

USA: +1 408.273.4530

Web: www.iqdfrequencyproducts.com