

OUTPUT

Frequency
160 MHz

Level
+13 dBm ± 2 dB into 50 ohms

STABILITY**Aging**

1×10^{-6} first year
after 30 days operating, typical
 5×10^{-7} second year, typical
 3×10^{-7} per year thereafter, typical

Phase Noise L(f), Static

100 Hz -123 dBc/Hz
1 kHz -143 dBc/Hz
10 kHz -161 dBc/Hz
100 kHz -162 dBc/Hz

Temperature Stability

$\pm 5 \times 10^{-7}$, 0° to +50°C (Ref +25°C)

Harmonics

≤ -25 dBc

Sub-Harmonics

≤ -50 dBc

Non-Harmonic Spurious

≤ -80 dBc, excluding power supply line related spurs

MECHANICAL**Dimensions**

2" x 2" x 1.3"

Connectors

SMA(f) and solder pins on one side

Packaging

Nickel-plated machined aluminum housing (CVP-1A)

Mounting

Threaded inserts, # 2-56, 4 places
Tapped holes on sides, 16 places (provisions for shock mounts)

POWER REQUIREMENTS**Warm-Up Power**

≤ 7 Watts for 5 minutes at +25°C

Total Power

≤ 4 Watts at +25°C

Supply Voltage

+15 VDC $\pm 5\%$

ADJUSTMENT**Mechanical Tuning**

$\pm 4 \times 10^{-6}$

Electrical Tuning

$\pm 5 \times 10^{-7}$ min, ± 5 VDC

Negative slope

CRYSTAL**Type**

80 MHz SC-cut w/ x2 stage

Acceleration Sensitivity

$\leq 5 \times 10^{-10}$ /g per axis, typical

ENVIRONMENTAL**Operating Temperature**

0° to +50°C

Storage Temperature

-40° to +85°C


OTHER**Label**

Use conventional label with the following information:
501-26955 (Current Rev.)
160 MHz Citrine Plus
+15 VDC
Serial # - Date Code

Test Data

Output Level
Phase Noise – Static
Temperature Stability
Harmonics, Subs, Spurious
Power - Warm-up and Total
Tuning – MT and ET

REV	DATE	REVISION RECORD	DWN	AUTH
-	06-25-13	Initial Release	PAC	

**Wenzel Associates, Inc.**

Austin, Texas

Title:

Standard 160 MHz Citrine Plus Crystal Oscillator

P/N:

501-26955

Rev:

-

Date:

06-25-13

Drawn:

Ref:

SPR

Tolerances:
(except as noted)
Dimensions are in inches

0.XX Dec:
 ± 0.030 "

0.XXX Dec:
 ± 0.010 "

FSCM:
62821

Page 1 of 1