



ZONE		REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 3.30-4.90 GHz
 Waveguide Size: WR229 (Input)
 Flange Types: Per Order (-1 to -10)
 VSWR: 1.15 Max.
 Average Power: 4000 Watts

F = FLANGE TYPES

- 1 = CPRG
- 2 = CPRF
- 3 = CMR STANDARD
- 4 = CMR THRU
- 5 = CMR TAP
- 6 = UG-COVER
- 7 = UG-CHOKE
- 8 = UG-COVER/GROOVE
- 9 = PDR
- 10 = UDR

FLANGE TYPE PER ORDER
 (WR229 CPRF SHOWN)

ORDERING INFORMATION

EXAMPLE PART NUMBER: WL-5-F
 VERY HIGH POWER SERIES
 FREQUENCY BAND
 FLANGE TYPE

Aluminum 6061 High Temp. Black Paint	MCLI MILLER COMMUNICATIONS LABORATORIES 7200 20TH AVE. S. LAKE WASHINGTON, WA 98148 TEL: (206) 344-1200 FAX: (206) 381-0110 WWW: WWW.MCLI.COM	QUANTITY: 1 ORDER NO.: DATE: 05-03-2011 APPROVED: T. Nguyen	ORDER NO.: DATE: 05-03-2011 APPROVED:	PART NO.: WL-5-F DESCRIPTION: TERMINATION, WR229 4000 Watts	QUANTITY: ORDER NO.: DATE: 05-03-2011 APPROVED:	PART NO.: OD2L5 DESCRIPTION: DO NOT SCALE THE DRAWING	QUANTITY: ORDER NO.: DATE: 05-03-2011 APPROVED:	PART NO.: 85654
---	--	--	---	--	--	--	--	---------------------------