

ISSUE 4; December 2014 - RoHS 2011/65/EU
Description

- Low EMI Spread Spectrum surface mount crystal oscillator in a ceramic package hermetically sealed with a seam sealed metal lid
- $\pm 0.125\%$ Centre Spread
- $\pm 0.25\%$ Centre Spread
- $\pm 0.5\%$ Centre Spread
- $\pm 1\%$ Centre Spread
- $\pm 2\%$ Centre Spread
- -0.25% Down Spread
- -0.5% Down Spread
- -1% Down Spread
- -2% Down Spread
- -4% Down Spread

Frequency Parameters

- Frequency 1.0MHz to 166.0MHz
- Frequency Stability $\pm 25.00\text{ppm}$ to $\pm 100.00\text{ppm}$
- Ageing $\pm 3\text{ppm}$ max per year

Electrical Parameters

- Supply Voltage 2.5V $\pm 5\%$
- Internal Spread Spectrum Modulation Frequency: 30kHz to 40kHz

Operating Temperature Ranges

- -10 to 70°C
- -40 to 85°C

Output Details

- Output Compatibility CMOS
- Drive Capability 15pF max
- Modulation Ratios:
Centre Spread $\pm 0.125\%$, $\pm 0.25\%$, $\pm 0.5\%$, $\pm 1\%$, $\pm 2\%$
Down Spread -0.25% , -0.5% , -1% , -2% , -4%

Output Control



- Standby Operation:
Logic '1' to pad 1 enables oscillator output
Logic '0' to pad 1 disables oscillator output, the oscillator output goes to a high impedance state
No connection to pad 1 enables oscillator output
- Standby Current: 10 μA max

Noise Parameters


- Cycle to Cycle Jitter (1- σ): 100ps max

Environmental Parameters

- Storage Temperature Range: -55 to 125°C
- Shock: 1500G, 0.5ms, 3 times in each of 3 mutually perpendicular planes
- Vibration: 20G, 20-2000Hz, 1.52mm amplitude, 4 cycles of 20mins in 3 mutually perpendicular planes (total 4hrs)

Outline (mm)

Test Circuit


* Inclusive of jigging and equipment capacitance

Example Output Spectrum (Centre Spread $\pm 1\%$)

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: +49 (0) 30 408 192 300

France: +33 (0)5 34 50 91 18
USA: +1 408.273.4530

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

