



Model: AE-B000-40D

Description:.....	Digital Controlled PIN Attenuator
Operating Frequency:.....	350 - 1100 MHz
Phase-Invariant Frequency Region (<±10 Deg)..	540 - 890 MHz
Insertion Loss (0dB Attn. Ref.):.....	1.7 dB Max
Attenuation Range:.....	0 – 40 dB Nominal Min
Attenuation Flatness:.....	0.6 dB Peak-Peak up to 10 dB
.....	1.0 dB Peak-Peak up to 20 dB
.....	1.4 dB Peak-Peak up to 30 dB
.....	1.6 dB Peak-Peak up to 40 dB
Control Function:.....	8 Bit Positive Binary TTL
.....	(LSB=0.25 dB, MSB=32 dB)
Transfer Function Accuracy:.....	0 – 0.8 dB ±50% Max
.....	> 0.8 – 10 dB ±0.40 dB Max
.....	>10 - 30 dB ±0.50 dB Max
.....	> 30 - 40 dB ±0.90 dB Max
VSWR (all settings):.....	1.5:1 Max
Settling Time ("±1dB of Target Setting"):.....	750 ns Max, (10µs<PW<0.1s)
Power Handling:.....	Operating..... +12 dBm CW/Peak Max
.....	Survival..... +30 dBm CW/AVG Max
Connectors (RF):.....	SMA (f), Removable
Connector (Supply & Controls):.....	15-Pin D-Type Male
Temperature Coefficient (Over Operating Temperature).....	±0.025 dB/°C Max
Power Supply (internally regulated):.....	+12 to +15vdc @ 60mA Max
.....	-12 to -15vdc @ 60mA Max
Impedance:.....	50 Ohms Nominal
Quality:.....	Best-Commercial-Grade

Environmental Ratings:

Temperature:.....	{Operating: -40°C to +85°C} & {Storage: -50°C to +100°C}
Humidity:.....	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:.....	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:.....	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:.....	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:.....	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ RF Connectors

- B1 [J1 SMA (male)]
- B2 [All SMA (male)]

■ Transfer Functions

- F3 [Inverse Logic ("00...00" = Max Attenuation)]

■ Control Function Resolution


- E1 [LSB = 1/8 dB <> 9-Bits <> "fractional steps"]
- R1 [LSB = 0.1 dB <> 9-Bits <> "decimal steps"]
- E2 [LSB = 1/16 dB <> 10-Bits <> "fractional steps"]
- R2 [LSB = 0.05 dB <> 10-Bits <> "decimal steps"]
- E3 [LSB = 1/32 dB <> 11-Bits <> "fractional steps"]
- E4 [LSB = 1/64 dB <> 12-Bits <> "fractional steps"]



Model: AE-B000-40D

Outline

(Tolerances: $\pm 0.015"$ [0.38mm])



Pin-Out Function

PIN	Function
1	N/C
2	N/C
3	N/C
4	N/C
5	0.25 dB
6	0.5 dB
7	1.0 dB
8	2.0 dB
9	4.0 dB
10	8.0 dB
11	16.0 dB
12	32.0 dB
13	+VDC
14	-VDC
15	GND (Chassis & Digital)

