



# AMP2044 SOLID STATE HIGH POWER AMPLIFIER



## FEATURES

- Rack mounted system
- Class AB solid-state linear design
- Instantaneous wide bandwidth
- Suitable for all modulations standards
- Built-in protection circuits
- High reliability and ruggedness

## ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	800 - 2000 MHz	
Power Output	200 Watt Min	CW
Power Output @ P1dB	150 Watt Min	
Small Signal Gain	54 dB Min	
Small Signal Gain Flatness	4.0 dB p-p Max	Constant input power
Input Return Loss	10 dB Min	Relative to 50 Ohm
3rd Order Intercept	+62 dBm Typ	
Harmonics	20 dBc Typ	At 150 Watt
Non Harmonics Spurious	60dBc Min	
Operating Voltage	100 - 240 VAC	
Power Consumption	1500 Watt Max	At rated Pout
Max Input Power	+10 dBm	Without damage
Load VSWR Protection	$\infty : 1$	

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensing
Shock and Vibrations	Normal truck transport	
Altitude	10,000 feet Min	

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 560 mm	3U
Weight	20 kg.	
RF Connectors In / Out	Type-N Female	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, GPIB Interface	Remote Bluetooth application

# AMP2044 SOLID STATE HIGH POWER AMPLIFIER

## OUTLINE DRAWING

