



WR284 WAVEGUIDE 3000W HIGH POWER TERMINATION - RFWT284D

1.0 Mechanical Specifications		
1.1	Waveguide type	Rectangular Waveguide WR284
1.2	Flange type	CPRF, COVER
1.3	Flange Holes	Through
1.4	Basis-material	Alloyed Cuprum
1.5	Internal Body Finish	Silver Plated chromate or conversion
1.6	External Body Finish	Body painted with gray/black epoxy enamel

2.0 Environment specifications		
2.1	Operation Temp.	-40°C~+85°C
2.2	Storage Temp.	-50°C~+125°C
2.3	Altitude	45000 ft
2.4	Vibration	10g rms (15 degree 2KHz)
2.5	Humidity	100% RH at 35c, 95%RH at 40 deg c
2.6	Shock	20G for 11msc

3.0 Electrical Specifications		
3.1	Frequency Range	2.6~3.95GHz
3.2	Average Power	3000W (CW)
3.3	Peak Power	2000kw
3.4	VSWR	1.10:1 (max)

PAGE 1 OF 1

DATE Jun 21st 2006

PROPRIETARY INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF RF-LAMBDA EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITINGS BY RF-LAMBDA. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN THE WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION OF ALL THIRD PARTIES AND SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY

DESIGN RFPC

RF-LAMBDA RFPC

CAD MODEL REVISION 11

ASSEMBLY REVISION VS5DS

ASSEMBLY NAME RFLVR05

DRAWING NUMBER D05-1

www.rflambda.com

RF-LAMBDA

RFWT284D WAVEGUIDE TERMINATION

SIZE LT SHEETS 1 OF 1