

SPECIFICATION SHEET
JFW MODEL 50DR-128
DUAL ROTARY ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-2500 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-30 dB in 1 dB steps
VSWR	1.5:1 maximum DC-2000 MHz 1.7:1 maximum 2000-2500 MHz
Insertion Loss	1.1 dB maximum
Attenuation Accuracy	± 0.5 dB or 3% DC-2000 MHz ± 0.5 dB or 4% 2000-2500 MHz (whichever is greater)
RF Input Power	2 Watts average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
RF Connector	SMA, TNC, or N female
Operating Temperature Range	-20°C to +85°C
Knob/Panel Mounting Drawing	092-8435-02
Outline Drawing	092-1748 (50DR-128 SMA)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	05/24/2011		TRS 05/24/2011				
20322	07/13/2011	A	TRS 07/13/2011				
25776	09/28/2015	B	TRS 09/29/2015				